



KEDRON Smart Deadbolt Lock with Fingerprint Access

This sleek, intelligent and feature-packed trade-grade smart deadbolt lock can be retrofitted to most existing deadbolt installations



Australian Registered Design
No. 202513993

mcgrathlocks.com.au

Technical Specifications

Hardware

| | |
|----------------------|---|
| Colour | Matt black or satin nickel |
| Type | Timber door, aluminium door |
| Door thickness | 35mm to 60mm (can extend up to 100mm with additional tailbar) |
| Durability test | 200,000 cycles |
| Material | Aluminium alloy, glass screen with fingerprint reader |
| Lock Case dimensions | Outside 165mm (H) x 71mm (W) x 28mm (D) Inside 166.5mm (H) x 73.5mm (W) x 38.7mm (D) (including turn knob) |

Enrolment and Verification

| | |
|--------------------|--|
| Unlocking method | PIN code, RFID credential (Mifare), Fingerprint, Bluetooth, Wi-Fi (Gateway required), mechanical key |
| Support system | Android - 4.3 / iOS 7.0 and above |
| Platforms | TTLock, TTHotel |
| App | McGrath Locks |
| Communication mode | Bluetooth 5.0 BLE and above |

Lock Features and Functions

| | |
|-----------------------------|---|
| Length of password | 4-9 digits (Minimum of 4 digits available when set via app) |
| Passage mode | Yes |
| Bluetooth capacity (eKeys) | Unlimited |
| PIN code capacity | 250 codes (some exceptions may apply) |
| RFID capacity | 1000 (some exceptions may apply) |
| Fingerprint capacity | 100 |
| Emergency opening | Rekeyable mechanical key override, USB-C (Power bank) |
| Batteries | 4 x AA Alkaline batteries (not included) |
| Stand-by power consumption | <66mA |
| Lock type | SS304 adjustable 60 - 70mm anti-saw bolt |
| Unlock time | 1.5s |
| Motor working current | Less than 200mA |
| Card working frequency | 13.56MHz |
| Battery life | 12 months (based on 10 uses per day) |
| Battery voltage | 4.5V-9V |
| Low battery warning voltage | Lower than 4.8V |

Operating Environment

| | |
|-------------------|--|
| Environment | -20°C to 70°C |
| Humidity | 0% - 80% RH |
| IP class | IP65 on external lock housing |
| Salt spray rating | 300 hour salt spray tested for black finish 96 hour salt spray tested for satin nickel finish |

| | |
|---|------------------|
| Warranty | 24 months |
| Australian Registered Design No. | 202513993 |

