Discreet with no external branding or markings Reversible door

Powder coated mild steel 1.5mm

Galvanised mounting plate installed

Manufactured in Europe

Accessories

Features

•

•

• IP66, IK10 rating

- Keyed Lock
- Adjustable pole clamps
- Vented front door, IP54

Specifications

Model	Sizing(WxDxH)	Description
RBMSB202015	200x150x200mm	IP66, 1.5mm Mild steel enclosure
RBMSB303020	300x200x300mm	IP66, 1.5mm Mild steel enclosure
RBMSB403020	300x200x400mm	IP66, 1.5mm Mild steel enclosure
RBMSB403025	300x250x400mm	IP66, 1.5mm Mild steel enclosure
RBMSB604020	400x200x600mm	IP66, 1.5mm Mild steel enclosure
RBMSB806020	600x200x800mm	IP66, 1.5mm Mild steel enclosure

Model	Description	
Vented door for mild steel enclosure		
RBMSVD2020	IP54, vented door for MSB.202015 (1x Vent)	
RBMSVD3030	IP54, vented door for MSB.303020 (1x Vent)	
RBMSVD4030	IP54, vented door for MSB.403020/25 (2x Vent)	
RBMSVD6040	IP54, vented door for MSB.604020 (2x Vent)	
RBMSVD8060	IP54, vented door for MSB.806020 (4x Vent)	
Pole Clamps		
RBBT2MSG200	Galvanized/Zinc pole clamp for MSB.202015, 100mm to 300mm pole diameter (200 wide cabinet) (150Kgs)	
RBBT2MSG300	Galvanized/Zinc pole clamp for MSB.303020, 100mm to 300mm pole diameter (300 wide cabinet) (150Kgs)	
RBBT2MSG400	Galvanized/Zinc pole clamp for MSB.402020/25, 100mm to 300mm pole diameter (400 wide cabinet) (150Kgs)	
RBBT2MSG600	Galvanized/Zinc pole clamp for MSB.806020, 100mm to 300mm pole diameter (600 wide cabinet) (150Kgs)	
Keyed lock		
RBSTPK2	Chromed keyed lock for MSB and SSB cabinets, (1x for 200-400 high, 2x for 600-800 high)	

Specifications are subject to change without prior notice.

Compact Enclosure - MSB Manufactured in Europe







