

## ASCOT Double Sided Gate Lock

Suited to gates and most types of doors that require a digital lock to be locked from both sides.



## Technical specifications

Hardware	
Colour	Satin chrome, polished chrome, black
Туре	Gates, timber door, aluminium door
Door thickness	35mm-55mm
Durability test	200,000 cycles
Material	Aluminium alloy, tempered glass screen
Spindle size	8mm
Lock case dimensions	75mm

Enrolment and Verification	
Unlocking method	Pin code, RFID credential, Bluetooth, WIFI (Gateway required)
Support system	Android - 4.3 /IOS 7.0 and above
Platforms	TTLock, TTRenting, TTHotel
Communication mode	Bluetooth 5.0 BLE and above

Lock Features and Functions		
Length of password	4-9 digits (Minimum of 4 digits available when set via APP)	
Passage mode	Yes	
Bluetooth capacity (eKeys)	Unlimited	
Pin code capacity	250 codes (Some exceptions may apply)	
RFID capacity	1000 (Some exceptions may apply)	
Emergency opening	Mechanical key override	
Batteries	4 x AAA Alkaline batteries per handle (Not included)	
Stand-by power consumption	<30mA	
Lock type	Tubular latch or mortice lock	
Unlock time	1.5s	
Motor working current	Less than 200mA	
Card working frequency	13.56MHz	

Battery life 12 months (Based on 10 uses per day)

Battery voltage 4.5V-8V

Low battery warning voltage Lower than 4.8V

Operating Environment		
Environment	-20°C to 70°C	
Humidity	10%-97% RH	
IP Class	IP66	

Warranty 24 months

Australian Registered Design No. 202215177



